


HD-PE TEE

Reinforced

for butt welding molded from PE100

对接正三通



OD (mm)	H (mm)	L (mm)	L ₁ (mm)	L ₂ (mm)	B (mm)	SDR17 ISO S8 PN10	SDR11 ISO S5 PN16
						S (mm)	S (mm)
20	38	76	15	40	21.0	1.8	2.0
25	42	84	15	50.0	26.0	1.8	2.3
32	46	92	17	55.0	33.4	2.0	2.9
40	51	102	15	71.5	45.2	2.4	3.7
50	58	116	23	76.0	54.0	3.0	4.6
63	66	132	27	96.0	65.0	3.8	5.8
75	75	150	28	120.0	76.8	4.5	6.8
90	90	180	32.5	117.0	93.5	5.4	8.2
110	110	220	34.5	148.5	114.0	6.6	10.0
125	119.5	239	35	169.0	133.0	7.4	11.4
140	140	280	35	182.0	150.0	8.3	12.7
160	160	320	35	204.0	170.0	9.5	14.6
180	158.5	317	35	247.0	190.0	10.7	16.4
200	168	336	35	266.0	210.0	11.9	18.2
225	220	440	40	260.0	235.0	13.4	20.5
250	209	418	45	328.0	262.0	14.8	22.7
280	318	636	70	374.0	284.0	16.6	25.4
315	353	706	70	410.0	331.0	18.7	28.6
355	348.3	696.56	152.1	392.4	371.5	21.1	32.2