


PVDF PIPE

Liner, PN10, PN16, PN20

for butt welding Tekwelding IR-welding

BCF-welding socket welding

直管



OD (mm)	LINER		SDR33 ISO S16 PN10		SDR21 ISO S10 PN16		SDR17 ISO S8 PN20	
	S (mm)	Weight (kg/m)	S (mm)	Weight (kg/m)	S (mm)	Weight (kg/m)	S (mm)	Weight (kg/m)
16	-	-	-	-	-	-	1.5	0.14
20	-	-	-	-	1.9	0.21	1.9	0.21
25	-	-	-	-	1.9	0.27	1.9	0.27
32	2.4	0.44	-	-	2.4	0.44	2.4	0.44
40	2.4	0.55	-	-	2.4	0.55	2.4	0.55
50	2.5	0.73	-	-	3.0	0.85	3.0	0.85
63	2.5	0.93	2.0	0.72	3.0	1.09	3.8	1.29
75	2.5	1.11	2.3	1.03	3.6	1.55	4.5	1.83
90	2.8	1.48	2.8	1.48	4.3	2.22	5.4	2.60
110	3.0	1.94	3.4	2.20	5.3	3.32	6.6	3.90
125	3.0	2.21	3.9	2.84	6.0	4.24	-	-
140	3.0	2.49	4.3	3.52	6.7	5.31	-	-
160	3.0	2.85	4.9	4.54	7.7	6.96	-	-
180	3.0	3.21	5.5	5.74	8.6	8.74	-	-
200	3.0	3.85	6.2	7.19	9.6	10.83	-	-
225	3.0	4.03	6.9	8.95	10.8	13.67	-	-
250	3.0	4.48	7.7	11.09	11.9	16.73	-	-
280	3.5	5.87	8.6	13.86	13.4	21.11	-	-
315	4.0	7.47	9.7	17.55	15.0	26.51	-	-
355	4.0	8.43	10.9	22.00	-	-	-	-
400	5.0	11.81	12.3	28.03	-	-	-	-
450	5.0	13.30	13.7	35.31	-	-	-	-
500	--	-	15.2	48.0	-	-	-	-
560	--	-	17.0	62.0	-	-	-	-
630	-	--	19.1	73.0	-	-	-	-