


## PVDF TEE

reinforced

for butt welding molded from PVDF

对接正三通



OD (mm)	H (mm)	L (mm)	L <sub>1</sub> (mm)	L <sub>2</sub> (mm)	B (mm)	SDR33 ISO S16 PN10	SDR21 ISO S10 PN16
						S (mm)	S (mm)
20	35.0	70.0	15.0	40.0	21.0	-	1.9
25	40.0	80.0	15.0	50.0	26.0	-	1.9
32	47.75	89.0	17.0	55.0	33.4	-	2.4
40	50.0	101.5	15.0	71.5	42.0	-	2.4
50	60.0	122.0	23.0	76.0	52.0	-	3.0
63	75.5	150.0	27.0	96.0	65.0	2.0	3.0
75	87.5	176.0	28.0	120.0	76.8	2.3	3.6
90	91.75	182.0	32.5	117.0	93.5	2.8	4.3
110	110.5	217.5	34.5	148.5	114.0	3.4	5.3
125	119.5	239.0	35.0	169.0	133.0	3.9	6.0
140	126.0	252.0	35.0	182.0	150.0	4.3	6.7
160	137.0	274.0	35.0	204.0	170.0	4.9	7.7
180	158.5	317.0	35.0	247.0	190.0	5.5	8.6
200	168.0	336.0	35.0	266.0	210.0	6.2	9.6
225	170.0	340.0	40.0	260.0	235.0	6.9	10.8
250	209.0	418.0	45.0	328.0	262.0	7.7	11.9
280	257.0	514.0	70.0	374.0	284.0	8.6	13.4
315	275.0	550.0	70.0	410.0	331.0	9.7	15.0