


## PVDF END CAP

elongated

for butt welding molded from PVDF

对接管帽



OD (mm)	L <sub>1</sub> (mm)	L (mm)	SDR33 ISO S16 PN10	SDR21 ISO S10 PN16
			S (mm)	S (mm)
20	30.0	42.0	-	1.9
25	35.0	50.0	-	1.9
32	40.0	55.0	-	2.4
40	40.0	60.0	-	2.4
50	40.0	60.0	-	3.0
63	50.0	70.0	2.0	3.0
75	55.0	80.0	2.3	3.6
90	60.0	90.0	2.8	4.3
110	65.0	100.0	3.4	5.3
125	70.0	110.0	3.9	6.0
140	106.0	144.0	4.3	6.7
160	118.5	142.0	4.9	7.7
180	141.0	191.0	5.5	8.6
200	127.0	181.0	6.2	9.6
225	141.5	210.0	6.9	10.8
250	152.0	230.0	7.7	11.9
280	162.0	257.0	8.6	13.4
315	180.0	262.0	9.7	15.0
355	75.0	130.0	10.9	-
400	75.0	130.0	12.3	-
450	75.0	130.0	13.7	-
500	75.0	130.0	15.2	-
560	75.0	130.0	17.0	-
630	100.0	160.0	19.1	-