


## PVDF END CAP

for socket welding  
molded from PVDF

套接管帽



| OD<br>(mm) | dsp <sup>±1.5</sup><br>(mm) | L <sup>±1.5</sup><br>(mm) | P<br>(mm) | SDR17<br>ISO S8<br>PN20 |
|------------|-----------------------------|---------------------------|-----------|-------------------------|
|            |                             |                           |           | Weight<br>(kg/Pc.)      |
| 16         | 24.1                        | 23.9                      | 14.5      | 0.012                   |
| 20         | 29.2                        | 26.9                      | 15.5      | 0.018                   |
| 25         | 35.1                        | 30.3                      | 17.0      | 0.029                   |
| 32         | 43.4                        | 35.0                      | 19.5      | 0.046                   |
| 40         | 52.1                        | 39.0                      | 21.6      | 0.069                   |
| 50         | 64.0                        | 49.0                      | 24.0      | 0.119                   |
| 63         | 81.0                        | 58.5                      | 28.2      | 0.236                   |
| 75         | 92.0                        | 65.5                      | 33.0      | 0.287                   |
| 90         | 112.5                       | 76.0                      | 37.0      | 0.535                   |
| 110        | 132.5                       | 92.0                      | 42.7      | 0.806                   |