


PP-H TEE

reinforced for
butt welding molded from PP-H
对接正三通



OD (mm)	H (mm)	L (mm)	L ₁ (mm)	L ₂ (mm)	B (mm)	SDR17.6 ISOS8.3 PN6	SDR11 ISOS5 PN10
						S (mm)	S (mm)
20	38.00	76.0	15.0	40.0	21.0	1.8	2.5
25	42.00	84.0	15.0	50.0	26.0	1.8	2.7
32	46.00	92.0	17.0	55.0	33.4	1.9	3.0
40	51.00	102.5	15.0	71.5	42.0	2.3	3.7
50	58.00	116.0	23.0	76.0	52.0	2.9	4.6
63	66.00	132.0	27.0	96.0	65.0	3.6	5.8
75	75.00	150.0	28.0	120.0	76.8	4.3	6.9
90	90.00	180.0	32.5	117.0	93.5	5.1	8.2
110	110.0	220.0	34.5	148.5	114.0	6.3	10.0
125	119.5	239.0	35.0	169.0	133.0	7.1	11.4
140	140.0	280.0	35.0	182.0	150.0	8.0	12.8
160	160.0	320.0	35.0	204.0	170.0	9.1	14.6
180	158.5	317.0	35.0	247.0	190.0	10.2	16.4
200	168.0	336.0	35.0	266.0	210.0	11.4	18.2
225	220.0	440.0	40.0	260.0	235.0	12.8	20.5
250	209.0	418.0	45.0	328.0	262.0	14.2	22.8
280	318.0	636.0	70.0	374.0	284.0	15.9	25.5
315	353	706	70	410	331	17.9	28.7
355	348.3	696.56	152.1	392.4	371.5	20.1	32.3