


PP-H END CAP

elongated

for butt welding molded from PP-H

对接管帽



OD (mm)	L (mm)	SDR17.6 ISO S8.3 PN6	SDR11 ISO S5 PN10
		S (mm)	S (mm)
20	52.0	1.8	2.5
25	52.0	1.8	2.7
32	54.0	1.9	3.0
40	57.0	2.3	3.7
50	71.0	2.9	4.6
63	65.0	3.6	5.8
75	80.0	4.3	6.9
90	90.0	5.1	8.2
110	98.0	6.3	10.0
125	110.0	7.1	11.4
140	136.0	8.0	12.8
160	122.0	9.1	14.6
180	191.0	10.2	16.4
200	181.0	11.4	18.2
225	150.0	12.8	20.5
250	230.0	14.2	22.8
280	257.0	15.9	25.5
315	262.0	17.9	28.7
355	130.0	20.1	32.3
400	130.0	22.7	36.4
450	130.0	25.5	41.0
500	150.0	28.3	45.5
560	150.0	31.7	50.9
630	160.0	35.7	57.2
710	160.0	40.2	64.5
800	160.0	45.5	72.7
900	160.0	51.2	81.8
1000	160.0	56.8	90.9
1200	160.0	68.1	109.0