


PP-H STUB FLANGE

acc. DIN 16962/16963

for butt welding molded from PP-H

法兰头



OD (mm)	h ₂ (mm)	L (mm)	d ₃ (mm)	d ₄ (mm)	SDR17.6 ISO S8.3 PN6		SDR11 ISO S5 PN10	
					S (mm)	h ₁ (mm)	S (mm)	h ₁ (mm)
20	29.0	50.0	26.0	45.0	1.8	7.2	1.9	7
25	27.0	52.0	32.0	58.0	1.8	9.2	2.3	9
32	28.0	54.0	40.0	68.0	1.9	10	2.9	10
40	25.0	56.0	49.0	78.0	2.3	11	3.7	11
50	32.0	62.0	60.0	88.0	2.9	12.2	4.6	12
63	38.0	68.0	75.0	102.0	3.6	14	5.8	14
75	43.0	80.0	88.0	122.0	4.3	16.1	6.9	16.1
90	41.0	80.0	104	138.0	5.1	17	8.2	17
110	40.0	80.0	124	158.0	6.3	18.2	10.0	18
125	102	175.0	135	158.0	7.1	25.5	11.4	25.5
140	39.0	89.0	155	188.0	8.0	27.4	12.7	25
160	45.0	92.0	175	212.0	9.1	26.2	14.6	25
180	127	180	186	217	10.2	26.5	16.4	26.5
200	144	213	229	268	11.4	31.5	18.2	31.5
225	35.0	100	235	268	12.8	33	20.5	32
250	205	275	284	320	14.2	34	22.8	34
280	35.0	100	291	320	15.9	32	25.5	35
315	35.0	100	335	370	17.9	35	28.7	35
355	140	203	373	430	20.1	40	32.3	40
400	140	203	427	482	22.7	40	36.4	40
450	140	216	514	585	25.5	50	41.0	50
500	140	216	530	585	28.3	50	45.5	50
560	140	220	615	685	31.7	55	50.9	55
630	140	220	642	685	35.7	55	57.2	55
710	150	246	737	800	40.2	55	64.5	55
800	150	248	840	905	45.5	60	72.7	60
900	150	260	944	1005	51.2	60	81.8	60
1000	150	260	1047	1110	56.8	70	90.9	70
1200	150	260	1245	1330	68.1	70	109.0	70