




PP-H REDUCED TEE

for socket welding
 molded from PP-H
 套接异径三通



OD (mm)	H (mm)	L (mm)	dsp ₁ (mm)	dsp ₂ (mm)	P ₁ (mm)	P ₂ (mm)	SDR11 ISO S5 PN10
							Weight (kg/Pc.)
25/20	32.0	68.5	35.1	29.1	17.5	15.5	0.04
32/20	40.0	80.5	43.1	29.1	19.6	15.5	0.05
32/25	40.0	80.5	43.1	35.1	19.6	17.5	0.06
40/20	45.0	90.5	52.2	29.1	21.6	15.5	0.08
40/25	45.0	90.5	52.2	35.1	21.6	17.5	0.08
40/32	45.0	91.5	52.2	43.1	21.6	19.6	0.10
50/20	52.5	110.5	64.2	29.1	23.6	15.5	0.16
50/25	52.5	110.5	64.2	35.1	23.6	17.5	0.16
50/32	52.5	107.0	64.2	43.1	23.6	19.6	0.17
50/40	52.5	107.0	64.2	52.2	23.6	21.6	0.17
63/25	65.0	128.6	81.3	35.1	28.1	17.5	0.27
63/32	64.5	128.6	81.3	43.1	28.1	19.6	0.27
63/40	64.5	128.6	81.3	52.2	28.1	21.6	0.28
63/50	64.5	128.6	81.3	64.2	28.1	23.6	0.28