



UPVC SCH40 管材



管材公称尺寸 inch	外径 inch(mm)	平均内径 inch(mm)	最小壁厚 inch(mm)	最大工作压力 W.P.PSI
1/2	0.840 (21.34)	0.602	0.109(2.77)	600
3/4	1.050 (26.67)	0.804	0.113(2.87)	480
1	1.315 (33.40)	1.029	0.133(3.38)	450
1-1/4	1.660 (42.16)	1.360	0.140(3.56)	370
1-1/2	1.900 (48.26)	1.590	0.145(3.68)	330
2	2.375 (60.32)	2.047	0.154(3.91)	280
2-1/2	2.875 (73.02)	2.445	0.203(5.16)	300
3	3.500 (88.90)	3.042	0.216(5.49)	260
4	4.500 (114.30)	3.998	0.237(6.02)	220
5	5.563 (141.30)	5.016	0.258(6.55)	190
6	6.625 (168.28)	6.031	0.280(7.11)	180
8	8.625 (219.08)	7.942	0.322(8.18)	160
10	10.750(273.05)	9.975	0.365(9.27)	140
12	12.750 (323.85)	11.889	0.406(10.31)	130
14	14.000(355.60)	13.073	0.437(11.10)	130
16	16.000(406.40)	14.940	0.500(12.70)	130
18	18.000(457.20)	16.809	0.562(14.27)	130
20	20.000(508.00)	18.743	0.593(15.06)	120
24	24.000(609.60)	22.544	0.687(17.45)	120