

CPVC SCH80 管材



管材公称尺寸 inch	外径 inch(mm)	平均内径 inch(mm)	最小壁厚 inch(mm)	最大工作压力 W.P.PSI
1/2	0.840 (21.34)	0.526	0.147 (3.73)	850
3/4	1.050 (26.67)	0.722	0.154 (3.91)	690
1	1.315 (33.40)	0.936	0.179 (4.55)	630
1-1/4	1.660 (42.16)	1.255	0.191 (4.85)	520
1-1/2	1.900 (48.26)	1.476	0.200 (5.08)	470
2	2.375 (60.32)	1.913	0.218 (5.54)	400
2-1/2	2.875 (73.02)	2.290	0.276 (7.01)	420
3	3.500 (88.90)	2.864	0.300 (7.62)	370
4	4.500 (114.30)	3.786	0.337 (8.56)	320
5	5.563 (141.30)	4.768	0.375 (9.52)	290
6	6.625 (168.28)	5.709	0.432(10.97)	280
8	8.625 (219.08)	7.565	0.500(12.70)	250
10	10.750(273.05)	9.493	0.593(15.06)	230
12	12.750 (323.85)	11.294	0.687(17.45)	230
14	14.000(355.60)	12.410	0.750(19.05)	220
16	16.000(406.40)	14.213	0.843 (21.41)	220
18	18.000(457.20)	16.014	0.937 (23.80)	220
20	20.000(508.00)	17.814	1.031 (26.19)	220
24	24.000(609.60)	21.418	1.218(30.94)	210